

perma Liquid grease SF06

Fluid grease for rolling and plain bearings subject to high loads

Advantages for your applications

- Good water resistance
- High wear protection
- Easy feedability

Description

perma Liquid grease SF06 is a multi-purpose fluid grease based on mineral oil.

It offers good water resistance and corrosion protection even at high temperatures.

Application

perma Liquid grease SF06 is used for the operational lubrication of bearings, guides and seals in the steel industry.

Due to its consistency this fluid grease is suitable for use in perma Lubrication Systems.

Application information


perma Liquid grease SF06 is a lubricant especially developed for the perma Lubrication Systems. To ensure adequate metering and maintenance-free lubrication, this product is only available in an perma Lubrication System.

Shelf life

Shelf life is approx. 12 months if the product is stored in its unopened original container in a dry and frost-protected place.

Packaging

- perma lubrication systems
- Cartridge 400 g
- Pail 1 kg
- Pail 5 kg



perma Liquid grease SF06

Fluid grease for rolling and plain bearings subject to high loads

Product data

Appearance	transparent
Chemical composition, thickener	aluminium complex soap
Chemical composition, type of oil	mineral oil
Density at 20 °C	approx. 0,88 g/cm ³
Colour space	brown
Lower service temperature	-20 °C / -4 °F
Upper service temperature	130 °C / 266 °F
Kinematic viscosity of the base oil, DIN 51562, 40 °C	approx. 220 mm ² /s
Kinematic viscosity, DIN 51562, 100 °C	approx. 19 mm ² /s
Speed factor (rpm x dm)	approx. 300 000
NLGI grade, DIN 51818	0
Texture	homogeneous
Texture	fibrous
Drop point, DIN ISO 2176	>= 210 °C